

## SilverNet Pico 95 Verkkosilta 95 Mbit/s Valkoinen

**Tuotemerkki** : SilverNet

**Tuotekoodi** : SIL PICO 95-PCP X6

**Tuotteen nimi** : Pico 95

SilverNet Pico 95. Tiedonsiirron enimmäisnopeus: 95 Mbit/s, Suurin siirtoetäisyys: 1000 m, Tuettu tiedonsiirtonopeus: 95Mbps. Antennin muotoilu: Sisäinen, Antennin vahvistustaso (maks.): 12 dBi, Panoroinnin/kallistusakselin alue: 180°. Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 1300 Mbit/s, Taajuuskaista: 5.1 - 5.8 GHz. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af. Yhteysteknologia: Langallinen & langaton



Data transmission		Features	
Maximum data transfer rate *	95 Mbit/s	Surge protection	✓
Maximum transfer distance	1000 m	Quality of Service (QoS) support	✓
Supported data transfer rates	95Mbps	Network Time Protocol (NTP) client	✓
Antenna		Mean time between failures (MTBF)	60000 h
Antenna design	Internal	System requirements	
Antenna gain level (max)	12 dBi	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Pan/tilt-axis range	180°	Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Antennas quantity	1	Power	
Wireless LAN features		Power source type	PoE
Wi-Fi	✓	AC input voltage	100 - 240 V
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Power supply	15.4 W
WLAN data transfer rate (max)	1300 Mbit/s	DC input voltage	24 - 48 V
Frequency band	5.1 - 5.8 GHz	Power consumption (typical)	6 W
Transmission gain	0 - 12 dB	Power consumption (max)	16 W
Signal strength	-40 dBm	Power over Ethernet (PoE)	✓
Channels quantity	25 channels	Power over Ethernet (PoE) voltage	48 V
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power plug type	Type G
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Operational conditions	
Output power (dBm)	26	Operating temperature (T-T)	-20 - 70 °C
Indoor range	1000m	Operating temperature (T-T)	-4 - 158 °F
Outdoor range	1000m	Operating relative humidity (H-H)	0 - 95%
Network		Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN	✓	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN interface type	Gigabit Ethernet	Certificates	
Ethernet LAN data rates	10,100,1000 Mbit/s	Certification	CE, FCC

<b>Network</b>		<b>Weight &amp; dimensions</b>	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af	Antenna diameter	16.5 cm
Cabling technology	10/100/1000Base-T(X)	Width	119 mm
Full duplex	✓	Depth	120 mm
Auto MDI/MDI-X	✓	Height	45 mm
Static IP	✓	Weight	300 g
Dynamic IP	✓	<b>Packaging content</b>	
<b>Ports &amp; interfaces</b>		PoE+ Injector(s)	✓
Connectivity technology	Wired & Wireless	Mounting bracket(s) included	✓
Ethernet LAN (RJ-45) ports	1	Power supply included	✓
<b>Security</b>		Antenna included	✓
Security algorithms	256-bit AES, 802.1x RADIUS, SNMPv2, SSH	Quick installation guide	✓
MAC address filtering	✓	<b>Other features</b>	
Authentication method	WPA2 AES	Commodity Classification Automated Tracking System (CCATS)	85176200
<b>Management features</b>		<b>Packaging data</b>	
Management protocols	SNMP V2	Package width	400 mm
Web-based management	✓	Package depth	340 mm
DHCP client	✓	Package height	580 mm
<b>Features</b>		Package weight	13.9 kg
Product type *	Network bridge	Package type	Box
Product colour	White	Quantity per pack	12 pc(s)
Remote control function	✓	<b>Logistics data</b>	
LED indicators	LAN, Signal strength	Country of origin	United Kingdom
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		
International Protection (IP) code	IP66		



5060693980480

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-JAN-2025. Prints or copies of Information are only valid on the printed Publication date