

## SilverNet Pico 95 Verkkosilta 95 Mbit/s Valkoinen

**Tuotemerkki :** SilverNet

**Tuotekoodi:** SIL PICO 95

**Tuotteen nimi :** Pico 95

SilverNet Pico 95. Tiedonsiirron enimmäisnopeus: 95 Mbit/s, Suurin siirtoetäisyys: 1000 m, Tuettu tiedonsiirtonopeus: 95Mbps. Antennin muotoilu: Sisäinen, Antennin vahvistustaso (maks.): 12 dBi, Panoroinnin/kallistusakselin alue: 180°. Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 1300 Mbit/s, Taajuuskaista: 5.1 - 5.8 GHz. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af. Yhteysteknologia: Langallinen & langaton



<b>Data transmission</b>		<b>Features</b>	
Maximum data transfer rate *	95 Mbit/s	International Protection (IP) code	IP66
Maximum transfer distance	1000 m	Surge protection	✓
Supported data transfer rates	95Mbps	Quality of Service (QoS) support	✓
<b>Antenna</b>		Network Time Protocol (NTP) client	✓
Antenna design	Internal	Mean time between failures (MTBF)	60000 h
Antenna gain level (max)	12 dBi	<b>System requirements</b>	
Pan/tilt-axis range	180°	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Antennas quantity	1	Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
<b>Wireless LAN features</b>		<b>Power</b>	
Wi-Fi	✓	Power source type	PoE
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	AC input voltage	100 - 240 V
WLAN data transfer rate (max)	1300 Mbit/s	Power supply	15.4 W
Frequency band	5.1 - 5.8 GHz	DC input voltage	24 - 48 V
Transmission gain	0 - 12 dB	Power consumption (typical)	6 W
Signal strength	-40 dBm	Power consumption (max)	16 W
Channels quantity	25 channels	Power over Ethernet (PoE)	✓
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power over Ethernet (PoE) voltage	48 V
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Power plug type	Type G
Output power (dBm)	26	<b>Operational conditions</b>	
Indoor range	1000m	Operating temperature (T-T)	-20 - 70 °C
Outdoor range	1000m	Operating temperature (T-T)	-4 - 158 °F
<b>Network</b>		Operating relative humidity (H-H)	0 - 95%
Ethernet LAN	✓	Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN interface type	Gigabit Ethernet	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN data rates	10,100,1000 Mbit/s		

Network		Certificates	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af	Certification	CE, FCC
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Full duplex	✓	Antenna diameter	16.5 cm
Auto MDI/MDI-X	✓	Width	119 mm
Static IP	✓	Depth	120 mm
Dynamic IP	✓	Height	45 mm
		Weight	300 g
Ports & interfaces		Packaging content	
Connectivity technology	Wired & Wireless	PoE+ Injector(s)	✓
Ethernet LAN (RJ-45) ports	1	Mounting bracket(s) included	✓
Security		Power supply included	✓
Security algorithms	256-bit AES, SNMPv2, SSH	Antenna included	✓
MAC address filtering	✓	Manual	✓
Authentication method	WPA2 AES	Quick installation guide	✓
Management features		Packaging data	
Management protocols	SNMP V2	Package width	300 mm
Web-based management	✓	Package depth	130 mm
DHCP client	✓	Package height	100 mm
Features		Package weight	985 g
Product type *	Network bridge	Package type	Box
Product colour	White	Quantity per pack	1 pc(s)
Remote control function	✓	Logistics data	
LED indicators	LAN, Signal strength	Country of origin	United Kingdom
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		



5060693980008

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAR-2025. Prints or copies of Information are only valid on the printed Publication date