

SilverNet SIL TDD60M21-PCP bridge/repeater Network bridge 1000 Mbit/s

Brand : SilverNet

Product code: SIL TDD60M21-PCP

Product name : SIL TDD60M21-PCP

PTP Bundle using MH-BU and 3-Port MH-TU inc MK & POE 1Gbps Capacity

[SilverNet SIL TDD60M21-PCP bridge/repeater Network bridge 1000 Mbit/s:](#)

SilverNet TDD60M products operate in the widely available and license exempt 60GHz V Band and deliver multi Gigabit throughputs.

In addition to the industry leading 400 meters range in PtMP configuration, the 60GHz Shorthaul series integrates advanced beam forming meaning there is no alignment necessary between the Base Unit and the Terminal Unit. This plug and play installation coupled with zero-touch configuration approach means shorthauled networks can be deployed rapidly and cost effectively by a single person.

SilverNet SIL TDD60M21-PCP. Maximum data transfer rate: 1000 Mbit/s, Maximum transfer distance: 250 m. Antenna design: Internal. Frequency band: 57-64 GHz, Transmission gain: 128 - 128.5 dB. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 100,1000 Mbit/s, Cabling technology: 10/100/1000Base-T(X). Connectivity technology: Wired & Wireless



Data transmission		Power	
Maximum data transfer rate *	1000 Mbit/s	Power source type	PoE
Maximum transfer distance	250 m	Power supply	10 W
Antenna		Power consumption (typical)	26 W
Antenna design	Internal	Power consumption (max)	55 W
Wireless LAN features		Power over Ethernet (PoE)	✓
Frequency band	57-64 GHz	Operational conditions	
Transmission gain	128 - 128.5 dB	Operating temperature (T-T)	-33 - 55 °C
Network		Certificates	
Ethernet LAN	✓	Certification	US FCC 47 CFR Part 15.255; Japan Radio Equipment Certification Ordinance 2-1-19-4-2 EMC: US FCC 47 CFR Part 15; EN 301 489 Safety: EN 62368-1 and 60950
Ethernet LAN interface type	Gigabit Ethernet		
Ethernet LAN data rates	100,1000 Mbit/s		
Cabling technology	10/100/1000Base-T(X)		
Ports & interfaces		Weight & dimensions	
Connectivity technology	Wired & Wireless	Width	130 mm
Ethernet LAN (RJ-45) ports	2	Depth	90 mm
Security		Height	190 mm
Security algorithms	128-bit AES	Weight	1.36 kg
Management features		Packaging content	
Management protocols	TU Auto-Provisioning; In-Band, Out-Of-Band Management; Web GUI; Embedded CLI; SNMPv2/3; TACACS+; RADIUS	PoE+ Injector(s)	✓
		Mounting bracket(s) included	✓
Web-based management	✓	Power supply included	✓
Data link protocols	Jumbo Frames; Port Isolation; TU Isolation; LLDP; Provider Bridge - VLAN & VLAN Stacking; IEEE 802.1d transparent bridging	Antenna included	✓
		Quick installation guide	✓
Features		Logistics data	
Product type *	Network bridge	UK Trade Tariff code	85176200
Mounting type	Pole/Wall		



5060693982118

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-MAR-2025. Prints or copies of Information are only valid on the printed Publication date