

## ASUS ProArt-RTX4070-O12G NVIDIA GeForce RTX 4070 12 GB GDDR6X

**Brand :** ASUS

**Product code:** 90YV0J11-M0NA00

**Product name :** ProArt-RTX4070-O12G



- NVIDIA Studio: RTX and AI-accelerated creator apps, exclusive AI software, and Studio Drivers for unmatched creativity and performance
  - NVIDIA Ada Lovelace Streaming Multiprocessors: Up to 2x performance and power efficiency
  - 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
  - 3rd Generation RT Cores: Up to 2x ray tracing performance
  - OC mode: 2565 MHz (OC mode)/ 2535 MHz (Default mode)
  - Axial-tech fans scaled up for 21% more airflow
  - 2.5-slot design: allows for greater build compatibility while maintaining premium cooling
  - Dual Ball Fan Bearings last up to twice as long as conventional designs
  - Auto-Extreme precision automated manufacturing for higher reliability
  - GPU Tweak III profile Connect enables creators to seamlessly optimize system performance and cooling for every app
- NVIDIA GeForce RTX 4070 12GB GDDR6X, PCI Express 4.0, 21 Gbps, 192-bit, 2.5 slot, 650W, 1 x 8-pin

Processor		Performance	
CUDA *	✓	Virtual Reality (VR) ready	✓
CUDA cores	5888	HDCP	✓
Graphics processor family *	NVIDIA	HDCP version	2.3
Graphics processor *	GeForce RTX 4070	Dual Link DVI *	✗
Processor boost clock speed	2535 MHz	NVIDIA G-SYNC	✓
Processor frequency (OC mode)	2565 MHz	Design	
Maximum resolution *	7680 x 4320 pixels	Cooling type *	Active
Parallel processing technology support *	Not supported	Cooling technology	ASUS Axial-tech
Maximum displays per videocard	4	Number of fans	3 fan(s)
Memory		Number of slots	2.5
Discrete graphics card memory *	12 GB	Product colour	Multicolour
Graphics card memory type *	GDDR6X	Power	
Memory bus *	192 bit	Minimum system power supply *	650 W
Memory bandwidth (max)	21 GB/s	Supplementary power connectors	1x 8-pin
Ports & interfaces		Weight & dimensions	
Interface type *	PCI Express 4.0	Weight	992 g
HDMI ports quantity *	1	Length	300 mm
HDMI version	2.1	Depth	50 mm
DisplayPorts quantity *	3	Height	120 mm
DisplayPort version	1.4a	Packaging data	
Performance		Package width	405 mm
OpenGL version *	4.6	Package depth	233 mm
		Package height	88.5 mm
		Package weight	1.65 kg
		Package type	Box



4711387301555



0197105301566



197105301566

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.