ASUS Dual GeForce GTX 1650 4GB GDDR6 EVO NVIDIA

Brand : ASUS Product family: Dual Product code: 90YV0EZE-M0NA00

Product name : Dual GeForce GTX 1650 4GB GDDR6 EVO

- The ASUS Dual GeForce® GTX 1650 is built with the breakthrough graphics performance of the award-winning NVIDIA TuringTM architecture to supercharge your favorite games
- Ultra-fast GDDR6 with over 50% more memory bandwidth for high-speed gaming
- GeForce Experience lets you capture and share videos, screenshots, and livestreams with friends, keep your GeForce drivers up to date, and easily optimize your in-game settings
- IP5X dust resistance offers protection from particle ingress for better durability
- Auto-Extreme Technology uses automation to enhance reliability
- 144-hour Validation Program puts cards through a series of stringent tests to ensure compatibility with the latest games
- GPU Tweak III provides intuitive performance tweaking, thermal controls, and system monitoring NVIDIA GeForce GTX 1650, 4GB GDDR6, 128 bit, PCI Express 3.0, $1 \times \text{HDMI}$ (2.0b), $1 \times \text{DVI-D}$, $1 \times \text{DP}$ (1.4a), CUDA, DirectX 12.0, OpenGL 4.6





| Processor | | Performance | |
|--|--|--|---|
| CUDA * CUDA cores 896 Graphics processor family * NVIDIA | 896 NVIDIA GeForce GTX 1650 1590 MHz | TV tuner integrated * DirectX version * OpenGL version * HDCP HDCP version Dual Link DVI * | x 12.0 4.6 v 2.2 |
| Maximum resolution * Parallel processing technology support * | 7680 x 4320 pixels Not supported | NVIDIA G-SYNC NVIDIA Ansel Design | , |
| Maximum displays per videocard Memory Discrete graphics card memory * Graphics card memory type * Memory bus * | 4 GB GDDR6 128 bit | Cooling type * Number of fans Form factor Number of slots Product colour | Active 2 fan(s) Full-Height/Half-Length (FH/HL) 2 Black |
| Ports & interfaces | 12 Gbit/s | Power Minimum system power supply * | 300 W |
| Interface type * HDMI ports quantity * HDMI version DVI-D ports quantity * DisplayPorts quantity * DisplayPort version | PCI Express 3.0 1 2.0b 1 1 1.4a | Supplementary power connectors Weight & dimensions Length Depth Height Packaging data | 1x 6-pin 212 mm 40 mm 121 mm |
| | | Package type | Вох |

