



DELL P7524QT Interactive flat panel 189.3 cm (74.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen

Brand : DELL

Product code: DELL-P7524QT

Product name : P7524QT

- 75" 4K UHD 3840 x 2160, IPS
- 8ms, 16:9, 350cd/m², 1200:1
- USB, HDMI, VGA , DisplayPort"
- 75" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m² 1.07 Billion, 8 ms, 178°/178°, 1200:1



DELL P7524QT Interactive flat panel 189.3 cm (74.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 75" 4K UHD large format monitor with 20-point touch, palm-rejection and built-in dual 20W speakers.
DELL P7524QT. Product design: Interactive flat panel. Display diagonal: 189.3 cm (74.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Product colour: Black



Display		Performance	
Panel type	IPS	Purpose *	Corporate
LED backlight	✓	On Screen Display (OSD)	✓
Display diagonal *	189.3 cm (74.5")	HID support	✓
Display technology *	LCD	Power	
Display resolution *	3840 x 2160 pixels	Power consumption (typical) *	140 W
Display brightness *	350 cd/m ²	Power consumption (standby) *	0.5 W
HD type *	4K Ultra HD	Power consumption (off)	0.3 W
Touchscreen *	✓	Power consumption (max)	290 W
Number of simultaneous touchpoints	20	Energy efficiency class (SDR)	G
Multi-touch	✓	Energy efficiency class (HDR)	Not available
Native aspect ratio	16:9	Energy consumption (SDR) per 1000 hours	140 kWh
Response time	8 ms	AC input voltage	100 - 240 V
Contrast ratio (typical)	1200:1	AC input frequency	50/60 Hz
Viewing angle, horizontal	178°	Heat dissipation	477.7 BTU/h
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours	1.07 billion colours	Computer system	
Pixel pitch	0.429 x 0.429 mm	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Display diagonal (metric)	189.273 cm	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
Horizontal scan range	30 - 140 kHz	Linux operating systems supported	✓
Vertical scan range	24 - 75 Hz	Weight & dimensions	
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Display width	1735 mm
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Display depth	79.1 mm
Hardness	9H	Display height	1017.4 mm
		Display weight	64 kg

Display		Packaging data	
Native refresh rate	60 Hz	Package weight	76.6 kg
RGB colour space	NTSC	Packaging content	
Colour gamut	72%	Remote control included	✓
Ports & interfaces		Stylus pen	✓
HDMI ports quantity *	3	Number of stylus pens	2
HDMI version	2.0	Cables included	AC, DisplayPort, HDMI, USB, VGA
DVI port *	✗	Operational conditions	
VGA (D-Sub) input ports	1	Operating temperature (T-T)	0 - 40 °C
DisplayPorts quantity *	1	Operating relative humidity (H-H)	10 - 80%
USB port *	✓	Storage temperature (T-T)	-20 - 60 °C
USB ports quantity	7	Storage relative humidity (H-H)	5 - 90%
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Operating altitude	0 - 5000 m
USB connector type	Mini-USB A	Non-operating altitude	0 - 12192 m
USB 2.0 Type-B ports quantity	3	Features	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Heat dissipation (max)	989.52 BTU/h
USB Type-C DisplayPort Alternate Mode	✓	Technical details	
Ethernet LAN *	✓	Sustainability compliance	✓
Ethernet LAN (RJ-45) ports	1	Sustainability certificates	ENERGY STAR
Wi-Fi *	✗	Doesn't contain	Arsenic, Mercury, PVC/BFR
Audio (L/R) in	1	Compliance certificates	RoHS
Audio (L/R) out	1	Other features	
RS-232 interface	✓	Quick start guide	✓
Audio		Cable lock slot	✓
Built-in speaker(s) *	✓	LED indicators	✓
Number of built-in speakers	2	On/off switch	✓
RMS rated power	40 W	Viewable size diagonal	18.9 cm
Design		Viewable size, horizontal	165 cm
Product design *	Interactive flat panel	Viewable size, vertical	92.8 cm
Placement supported *	Indoor	Power supply type	Internal
Product colour *	Black	Cable management	✓
Screen shape	Flat	Response time	8 s
VESA mounting *	✓	Plug and Play	✓
Panel mounting interface	400 x 400 mm		
Bezel width (bottom)	4.67 cm		
Bezel width (side)	4.27 cm		
Bezel width (top)	4.28 cm		
Anti-glare screen	✓		



5397184821558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date