PHILIPS

Philips Signage Solutions 37BDL3050S/00 infonäyttö 94 cm (37") 700 cd/m² Full HD musta Sisäänrakennettu prosessori Android 8.0 24/7




Tuotemerkki : Philips **Tuoteperhe:** Signage Solutions **Tuotekoodi:** 37BDL3050S/00

Tuotteen nimi: 37BDL3050S/00

Philips Signage Solutions 37BDL3050S/00. Näytön halkaisija: 94 cm (37"), Näytön erottelutarkkuus: 1920 x 540 pikseliä, Näytön kirkkaus: 700 cd/m², HD-tyyppi: Full HD. Toiminta-aika (tunteja/päiviä): 24/7. Käyttöjärjestelmä asennettu: Android 8.0. Tuotteen väri: musta

Dienlay		Performance	
Display		Performance	
Display diagonal * Display resolution * Display brightness * HD type * Native aspect ratio Response time	94 cm (37") 1920 x 540 pixels 700 cd/m ² Full HD 32:9 8 ms	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
		Operating hours (hours/days)	24/7
Contrast ratio (typical)	4000:1	Mean time between failures (MTBF)	50000 h
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Power consumption (typical) *	70 W
Pixel pitch	0.47 x 0.47 mm	Power consumption (standby) *	0.5 W
Ports & interfaces		Input voltage	100/240 V
HDMI ports quantity *	2	AC input voltage	100/240 V
HDMI version	2.0	AC input frequency	50 - 60 Hz
HDMI input ports quantity HDMI output ports quantity	1 1	Computer system	
		Built-in processor *	✓
VGA (D-Sub) input ports	1	Internal memory	2 GB
USB port *	•	On-board graphics card model Internal storage capacity	ARM Mali-G51
USB ports quantity	1		8 GB
USB version 2.0 USB connector type USB Type-A		Operating system installed	Android 8.0
	USB Type-A ✓ 1	Weight & dimensions	
Ethernet LAN * Ethernet LAN (RJ-45) ports		Display width	928.5 mm
PC Audio in	· ✓	Display depth	48.7 mm
RS-232 interface	v	Display height	282.3 mm
Remote (IR) input	1	Display weight	7.76 kg
Remote (IR) output	1	Packaging content	
·	-	Remote control included	✓
Design	ladaa	Batteries included	✓
Placement supported * Orientation	Indoor Horizontal	Cables included	AC, HDMI, IR sensor, RS-232
Product colour *	Black	Mounting kit	✓
VESA mounting *	J d d d d d d d d d d d d d d d d d d d	Operational conditions	
Panel mounting interface	400 x 200 mm	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	20 - 80%
		Storage temperature (T-T)	-20 - 60 °C
		Storage relative humidity (H-H)	5 - 95%
		Certificates	
		Certification	THIS FCC Class A CB





8712581799489

0810112790016



810112790016

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.