

## LG 22SM3G-B infonäyttö Digitaalinen litteä infotaulu 54,6 cm (21.5") IPS Wi-Fi 250 cd/m² Full HD musta Sisäänrakennettu prosessori 16/7

Tuotemerkki: LG Tuotekoodi: 22SM3G-B

Tuotteen nimi: 22SM3G-B

LG 22SM3G-B. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 54,6 cm (21.5"), Näytön teknologia: IPS, Näytön erottelutarkkuus:  $1920 \times 1080$  pikseliä, Näytön kirkkaus:  $250 \text{ cd/m}^2$ , HDtyyppi: Full HD. Wi-Fi. Toiminta-aika (tunteja/päiviä): 16/7. Tuotteen väri: musta





Display		Power	
Display diagonal * 54.6 cm (21.5")  Display technology * IPS  Display resolution * 1920 x 1080 pixels  Display brightness * 250 cd/m²  HD type * Full HD  Touchscreen * X  Native aspect ratio 16:9	IPS 1920 x 1080 pixels 250 cd/m² Full HD	Power consumption (typical) * Power consumption (standby) * Power consumption (sleep) Power consumption (off) AC input voltage AC input frequency Heat dissipation	33 W 30 W 1 W 0.5 W 100 - 240 V 50 - 60 Hz 7.89 BTU/h
Contrast ratio (typical)	1000:1	Computer system	
Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Display diagonal (metric)	400000:1 178° 178° 55.88 cm	Computer system * Built-in processor * Processor cores Internal memory	X ✓ 4 4 GB
Ports & interfaces	_	Weight & dimensions	
HDMI ports quantity * 2  DVI port *   USB port *   USB ports quantity 1	Width Depth Height Weight	510.3 mm 53.8 mm 302.1 mm 3.34 kg	
USB version	2.0	Packaging data	5
Ethernet LAN * Ethernet LAN (RJ-45) ports Wi-Fi * Audio (L/R) in RS-232 interface	1 1 1	Package width Package depth Package height Package weight	565 mm 103 mm 357 mm 3.5 kg
RS-232C	·	Packaging content	
Audio  Built-in speaker(s) *  Number of built-in speakers  RMS rated power	✓ 2 2 W	Remote control included Batteries included Cables included Mounting kit	✓ ✓ AC
Design		Operational conditions	
Product design * Orientation Product colour * VESA mounting *	Digital signage flat panel Horizontal Black	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 10 - 80% -20 - 60 °C 5 - 85%

Design		Certificates	
Panel mounting interface	100 x 100 mm	Certification	CB, NRTL, EMC, FCC Class "A", CE,
Performance			ErP
Purpose *	Universal 16/7	Logistics data	
Operating hours (hours/days)		Harmonized System (HS) code	85285210







0719192636200



719192636200



8806098661060

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.