**Canon**

Canon i-SENSYS LBP852Cx Väri 9600 x 600 DPI A3

Tuotemerkki : Canon   **Tuoteperhe:** i-SENSYS   **Tuotekoodi:** 1830C007

Tuotteen nimi : LBP852Cx

Canon i-SENSYS LBP852Cx. Väri. Suurin toimintajakso: 120000 sivua kuukaudessa. Suurin resoluutio: 9600 x 600 DPI. Suurin ISO A-luokan paperikoko: A3. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 36 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius

Printing

Colour *	✔
Duplex printing *	✔
Maximum resolution *	9600 x 600 DPI
Print speed (black, normal quality, A4/US Letter) *	36 ppm
Print speed (black, normal quality, A3)	18 ppm
Duplex print speed (black, normal quality, A4/US Letter)	36 ppm
Warm-up time	34 s
Time to first page (black, normal)	6.7 s
Time to first page (colour, normal)	7.4 s
Print margins (top, bottom, right, left)	5 mm

Features

Maximum duty cycle *	120000 pages per month
Recommended duty cycle	2500 - 7500 pages per month
Printing colours *	Black, Cyan, Magenta, Yellow
Page description languages *	PCL 5e, PCL 6, PostScript, UFRII
Number of printer fonts	241

Input & output capacity

Total number of input trays *	1
Total input capacity *	550 sheets
Total output capacity *	200 sheets
Paper input type	Cassette, Paper tray
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	100 sheets
Maximum number of input trays	4
Maximum input capacity	2200 sheets

Paper handling

Maximum ISO A-series paper size *	A3
Paper tray media types *	Coated paper, Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Rough paper
Multi-purpose tray media types	Executive, Legal, Letter
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6

Ports & interfaces

USB 2.0 ports quantity	4

Network

Network ready	✔
Wi-Fi *	✘
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s
Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service

Performance

Internal memory *	1000 MB
Maximum internal memory	1000 MB
Built-in processor	✔
Sound pressure level (printing)	52 dB
Sound pressure level (duplex printing)	51 dB
Sound power level (standby)	30 dB

Design

Built-in display *	✔
Display	LCD
Display number of lines	5 lines

Power

Power consumption (max)	1500 W
Power consumption (ready)	2 W
Power consumption (standby)	50 W
Energy Star Typical Electricity Consumption (TEC)	1.6 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz

System requirements

Windows operating systems supported	Windows 10, Windows 7, Windows 8.1

Paper handling

ISO B-series sizes (B0...B9)	B4, B5
Custom media width	64 - 320 mm
Custom media length	120 - 457.2 mm
Paper tray media weight	60 - 256 g/m²
Multi-Purpose Tray media weight	60 - 300 g/m²
Duplex media weight	60 - 163/100 - 220 g/m²

Ports & interfaces

USB port *	✔

System requirements

Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.9 Mavericks
Linux operating systems supported	✔
Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Operational conditions

Operating temperature (T-T)	10 - 30 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	556 mm
Depth	608 mm
Height	403 mm
Weight	45 kg

Logistics data

Harmonized System (HS) code	84433210

4549292148473