Canon

Canon imageFORMULA DR-C225W II ADF + Manuaalinen syöttöskanneri 600 x 600 DPI A4 musta

Tuotemerkki: Canon Tuoteperhe: imageFORMULA Tuotekoodi: 3259C003

Tuotteen nimi: DR-C225W II

Canon imageFORMULA DR-C225W II. Skannauksen enimmäiskoko: 216 x 356 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, Lähdön värisyvyys: 24 bittiä. Skannerityyppi: ADF + Manuaalinen syöttöskanneri, Tuotteen väri: musta. Anturin tyyppi: CMOS CIS, Päivittäinen käyttöjakso (maks.): 1500 sivua, Valonlähde: RGB LED. Suurin ISO A-luokan paperikoko: A4. Vakioliitännät: USB 2.0, Langaton LAN





Canning		Daway	
Scanning		Power	
Maximum scan size * Optical scanning resolution * Colour scanning Duplex scanning * Output colour depth Output greyscale depth	216 x 356 mm 600 x 600 DPI ✓ 24 bit 8 bit	Power supply type * Power consumption (typical) Power consumption (off) AC input frequency Input voltage Power consumption (sleep)	AC 15.6 W 0.5 W 50 - 60 Hz 100-240 V 4.4 W
ADF scan speed (b/w, A4)	25 ppm	Weight & dimensions	
ADF scan speed (colour, A4) Duplex ADF scan speed (b/w, A4) Duplex ADF scan speed (colour, A4) Design	25 ppm 50 ipm 50 ipm	Width Depth Height Weight	300 mm 156 mm 220 mm 2.6 kg
	ADF + Manual feed scanner		2.0 kg
Scanner type * Product colour *	Black	Packaging content	AC LICE
Built-in display *	X	Cables included Quick start guide	AC, USB ✓
Performance		AC adapter included	·
Sensor type *	CMOS CIS	·	•
Light source	RGB LED 1500 pages	Sustainability	ENERGY STAR
Daily duty cycle (max) *		Sustainability certificates	ENERGY STAR
Scan drivers	ISIS, TWAIN	System requirements	
Scanner error detection Ultrasonic double sheet detection Paper handling	*	Windows operating systems supported	Windows 10, Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP
Maximum ISO A-series paper size *	A4		Professional, Windows XP Professional x64
Ports & interfaces	AT.	Mac operating systems supported	✓
		Mobile operating systems supported	Android, iOS
USB port * USB version	2.0	Operational conditions	
Standard interfaces	USB 2.0, Wireless LAN	Operating temperature (T-T)	10 - 32.5 °C
Network	OSB 2.0, Willeless E. III	Operating relative humidity (H-H)	20 - 80%
Wi-Fi	•	Other features	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84716070



4528472108476

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.