Canon

Canon imageFORMULA DR-G2140 Sheet-fed scanner 600 x 600 DPI A3 Black, White

Brand : Canon

Product family: imageFORMULA

Product code: 3149C003

Product name : DR-G2140

A3, CIS, 600 dpi, RGB LED, 500 sheets, RJ-45, USB 3.1

Canon imageFORMULA DR-G2140 Sheet-fed scanner 600 x 600 DPI A3 Black, White:

Ultra-fast model takes production scanning to the next level

Optimised for customers who require exceptional high-speed productivity, superior image quality and dependable feeding performance, this A3 scanner has been created to excel in demanding environments

Productivity
Ultra-efficient scanner outputs up to 280 images per minute

Reliability
Robust, durable paper feed and transport rollers can deliver up to 70,000 scans per day

Image quality
Advanced image-processing tools deliver consistently crisp, clear, high-quality images

Scanning

Maximum scan size *	305 x 432 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Output colour depth	24 bit
ADF scan speed (b/w, A3)	145 ppm
ADF scan speed (colour, A3)	145 ppm
Duplex ADF scan speed (b/w, A4)	290 ipm
Duplex ADF scan speed (colour, A4)	290 ipm

Design

Scanner type *	Sheet-fed scanner
Product colour *	Black, White
Built-in display *	✔

Performance

Sensor type *	CIS
Light source	RGB LED
Daily duty cycle (max) *	70000 pages
Scanning noise level	54 dB

Input capacity

Standard input capacity	500 sheets

Paper handling

Long-paper mode	✔
Maximum ISO A-series paper size *	A3

Paper handling

Auto Document Feeder (ADF) media weight	20 - 209 g/m²

Ports & interfaces

USB port *	✔
USB version	3.2 Gen 2 (3.1 Gen 2)
Standard interfaces	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1)

Network

Ethernet LAN	✔

Power

Power supply type *	AC
Power consumption (typical)	66.5 W
Power consumption (standby)	3.5 W
AC input frequency	50 - 60 Hz
Input voltage	220 - 240 V

Weight & dimensions

Width	480 mm
Depth	569 mm
Height	315 mm
Weight	25 kg

Operational conditions

Operating temperature (T-T)	10 - 35 °C
Operating relative humidity (H-H)	20 - 80%
Operating temperature (T-T)	50 - 95 °F

Logistics data

Harmonized System (HS) code	84716070

4528472108131

0013803308303

013803308303