



## Canon imageFORMULA DR-C225 II ADF + Manual feed scanner 600 x 600 DPI A4 Black

Brand : Canon

Product family:  
imageFORMULA

Product code: 3258C003

Product name : DR-C225 II

FORMULA DR-C225 II, A4, CMOS CIS, 600 dpi, RGB LED, USB 2.0, 300x156x220 mm  
Canon imageFORMULA DR-C225 II. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, ADF scan speed (b/w, A4): 25 ppm. Scanner type: ADF + Manual feed scanner, Product colour: Black. Sensor type: CMOS CIS, Daily duty cycle (max): 1500 pages, Light source: RGB LED. Maximum ISO A-series paper size: A4. Standard interfaces: USB 2.0



<b>Scanning</b>		<b>Power</b>	
Maximum scan size *	216 x 356 mm	Power consumption (typical)	12.7 W
Optical scanning resolution *	600 x 600 DPI	Power consumption (off)	0.5 W
Colour scanning	✓	AC input frequency	50 - 60 Hz
Duplex scanning *	✓	Input voltage	100-240 V
ADF scan speed (b/w, A4)	25 ppm	Power consumption (sleep)	1.8 W
ADF scan speed (colour, A4)	25 ppm	<b>Weight &amp; dimensions</b>	
Duplex ADF scan speed (b/w, A4)	50 ipm	Width	300 mm
Duplex ADF scan speed (colour, A4)	50 ipm	Depth	156 mm
<b>Design</b>		Height	220 mm
Scanner type *	ADF + Manual feed scanner	Weight	2.8 kg
Product colour *	Black	<b>Packaging content</b>	
Built-in display *	✗	Cables included	AC, USB
<b>Performance</b>		Quick start guide	✓
Sensor type *	CMOS CIS	AC adapter included	✓
Light source	RGB LED	<b>Sustainability</b>	
Daily duty cycle (max) *	1500 pages	Sustainability certificates	ENERGY STAR
Scan drivers	ISIS, TWAIN	<b>System requirements</b>	
Scanner error detection	✓	Windows operating systems supported	Windows 10, Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Ultrasonic double sheet detection	✓	Mac operating systems supported	✓
<b>Paper handling</b>		Mobile operating systems supported	Android, iOS
Maximum ISO A-series paper size *	A4	<b>Operational conditions</b>	
<b>Ports &amp; interfaces</b>		Operating temperature (T-T)	10 - 32.5 °C
USB port *	✓	Operating relative humidity (H-H)	20 - 80%
USB version	2.0	<b>Other features</b>	
Standard interfaces	USB 2.0	Compliance certificates	RoHS
<b>Power</b>		<b>Logistics data</b>	
Power supply type *	AC	Harmonized System (HS) code	84716070



4528472108384



5415247303954

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.