

Canon i-SENSYS LBP352x 1200 x 1200 DPI A4

Tuotemerkki : Canon

Tuotepihe: i-SENSYS

Tuotekoodi: 0562C008

Tuotteen nimi : LBP352x



Canon i-SENSYS LBP352x. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 280000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaali-laatu, A4/US Letter): 62 ppm, Kaksipuolinen tulostus. Näyttö: LCD, Tuotteen väri: musta, Valkoinen

Printing		Network	
Duplex printing mode	Auto	Wi-Fi *	✗
Colour *	✗	Ethernet LAN *	✓
Print technology *	Laser	Web-based management	✓
Duplex printing *	✓	Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service
Maximum resolution *	1200 x 1200 DPI		
Print speed (black, normal quality, A4/US Letter) *	62 ppm		
Duplex print speed (black, normal quality, A4/US Letter)	41.4 ppm		
Warm-up time	29 s		
Time to first page (black, normal)	7 s		
Print margins (top, bottom, right, left)	5 mm		
Secure printing	✓		
Features		Performance	
Maximum duty cycle *	280000 pages per month	Internal memory *	1024 MB
Recommended duty cycle	5000 - 20000 pages per month	Built-in processor	✓
Number of print cartridges *	1	Processor frequency	528 MHz
Page description languages *	PCL 5e, PCL 6, URF	Sound pressure level (printing)	71 dB
Input & output capacity		Design	
Total number of input trays *	1	Product colour *	Black, White
Total input capacity *	500 sheets	Built-in display *	✓
Total output capacity *	500 sheets	Display	LCD
Paper input type	Cassette, Paper tray	Display number of lines	5 lines
Multi-Purpose tray	✓	Power	
Multi-Purpose tray input capacity	100 sheets	Power consumption (printing) *	850 W
Maximum number of input trays	4	Power consumption (max)	1650 W
		Power consumption (standby)	19 W
		Power consumption (off)	0.17 W
		Energy Star Typical Electricity Consumption (TEC)	2.8 kWh/week
		AC input voltage	220 - 240 V
		AC input frequency	50 - 60 Hz
Paper handling			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper		
ISO A-series sizes (A0...A9) *	A4, A5, A6		
ISO B-series sizes (B0...B9)	B5, B6		
Envelopes sizes	10, C5, DL, Monarch		
Custom media width	148 - 216 mm		
Custom media length	210 - 356 mm		
Paper tray media weight	60 - 120 g/m ²		
Multi-Purpose Tray media weight	60 - 199 g/m ²		
Duplex media weight	60 - 120 g/m ²		
Ports & interfaces			
Standard interfaces	Ethernet, USB 2.0		
Direct printing *	✓		
USB 2.0 ports quantity	1		

System requirements

Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64
Mac operating systems supported	Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	✓
Server operating systems supported	Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2

Operational conditions

Operating temperature (T-T)	10 - 30 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	415 mm
Depth	529 mm
Height	438 mm
Weight	26.2 kg

Logistics data

Harmonized System (HS) code	84433210
-----------------------------	----------

Other features

Power LED	✓
Print resolution	600 x 600 DPI



4549292051421

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.