

## Canon M40 1200 x 1200 DPI

**Tuotemerkki :** Canon

**Tuotekoodi:** 2886V298

**Tuotteen nimi :** M40

Canon M40. Skannauksen enimmäiskoko: 1067 x 15000 mm, Optinen skannauserottelutarkkuus: 1200 x 1200 DPI, Tehostettu skannaustarkkuus: 1200 x 1200 DPI. Näyttö: TFT, Näytön halkaisija: 49,5 cm (19.5"). Anturin tyyppi: CIS, Tiedostomuodot (skanneri): JPG, PDF, TIFF, Sisäinen muisti: 4000 MB. USB-versio: 3.2 Gen 1 (3.1 Gen 1), Vakioliitännät: USB 3.2 Gen 1 (3.1 Gen 1). Virtalähteen tyyppi: AC, Virrankulutus: 40 W, Virrankulutus valmiustilassa: 0,3 W



<b>Scanning</b>		<b>Power</b>	
Maximum scan size *	1067 x 15000 mm	Power supply type *	AC
Optical scanning resolution *	1200 x 1200 DPI	Power consumption (typical)	40 W
Enhanced scan resolution	1200 x 1200 DPI	Power consumption (standby)	0.3 W
Colour scanning	✓	AC input frequency	50 - 60 Hz
Duplex scanning *	✗	Input voltage	100-240 V
Input colour depth	24 bit	<b>Packaging content</b>	
Film scanning	✗	Cables included	USB
Greyscale levels	256	Quick start guide	✓
Black/white scanning colour modes	Grayscale	<b>Sustainability</b>	
<b>Design</b>		Sustainability certificates	ENERGY STAR
Display	TFT	<b>System requirements</b>	
Display diagonal	49.5 cm (19.5")	Windows operating systems supported	Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Touchscreen	✓	Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
<b>Performance</b>		<b>Operational conditions</b>	
Sensor type *	CIS	Operating temperature (T-T)	10 - 35 °C
Scan file formats	JPG, PDF, TIFF	Operating relative humidity (H-H)	35 - 80%
Internal memory	4000 MB	<b>Other features</b>	
Built-in processor	✓	Compatibility	iPF770, iPF780, iPF785, iPF830, iPF840, iPF850 iPF8400SE
Processor frequency	2.3 MHz	Compliance certificates	RoHS
<b>Ports &amp; interfaces</b>		Certification	CB, CE, FCC, UL
USB port *	✓	<b>Technical details</b>	
USB version	3.2 Gen 1 (3.1 Gen 1)	Panel type	TFT
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)		



8714574631264

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.