Canon

Canon i-SENSYS MF426dw Laser A4 1200 x 1200 DPI 38 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS

Product code: 2222C007

Product name : MF426dw

i-SENSYS MF426dw, 1200 x 1200 DPI, 38 ppm A4, 63.1 ppm A5, 30.3 ipm A4, 33.6 Kbps, ADF, USB 2.0, LAN, WLAN, 12.7cm LCD, 220-240 V 50 - 60 Hz, 453 x 464 x 392 mm

Canon i-SENSYS MF426dw Laser A4 1200 x 1200 DPI 38 ppm Wi-Fi:

Reliable, secure and easy-to-use all-in-one with fax printer for offices or SMEs with a multitude of functions.

The i-SENSYS MF420 series are multi-function printers offering SMEs speed, durability, and quality. Mobile connectivity maximises productivity.

Genuine all-in-one cartridge Makes printing easier and more reliable

High capacity 250-sheet tray for A4, A5 & A6

Simple to use Five-inch LCD colour touchscreen

Fast printing speeds Up to 38ppm print speed

Quick scanning Double-sided single pass scanning

Application library Customised and automated functions

High-quality

Up to 1200 x 1200 dpi resolution

Security Via PIN access to print

Printing		Input & output capacity	
Duplex printing mode	Auto	Multi-Purpose tray input capacity	100 sheets
Print technology *	Laser	Paper input type	Cassette, Paper tray
Printing *	Mono printing	Auto document feeder (ADF)	1
Duplex printing *	1	Auto document feeder (ADF) input	50 sheets
Maximum resolution *	1200 x 1200 DPI	capacity	50 sheets
Print speed (black, normal quality, A4/US Letter) *	38 ppm	Paper handling	
Duplex print speed (black, normal		Maximum ISO A-series paper size *	A4
quality, A4/US Letter)	30.3 ppm	Description of the large state	Envelopes, Heavy paper, Labels,
Warm-up time	14 s	Paper tray media types *	Plain paper, Recycled paper, Thin paper
Time to first page (black, normal) Print margins (top, bottom, right,	5.5 s	Multi-purpose tray media types	Envelopes, Executive, Legal, Letter, Plain paper
left)	5 mm	ISO A-series sizes (A0A9) *	A4, A5, A6
Secure printing	 Image: A set of the set of the	ISO B-series sizes (B0B9)	В5
Copying		Non-ISO print media sizes	16K
Duplex copying *	J.	Envelopes sizes	10, C5, DL, Monarch
1 1,9 5	-	Custom media width	76.2 - 215.9 mm
Copying *	Mono copying	Custom media length	127 - 355.6 mm
Maximum copy resolution *	600 x 600 DPI	Paper tray media weight	52 - 120 g/m²
Copy speed (black, normal quality, A4)	38 cpm	Auto Document Feeder (ADF) media weight	50 - 105 g/m²
Duplex copy speed (black, US Letter)	30.3 ppm	neight	





Copying		Ports & interfaces	
	6.6.c		Ethornot LICD 2.0 Minutes I AN
Time to first copy (black, normal) Maximum number of copies	6.6 s 999 copies	Standard interfaces	Ethernet, USB 2.0, Wireless LAN
Copier resize	25 - 400%	Direct printing *	
N-in-1 copy function	25 - 4 00 %	USB port	
N-in-1 copy function (N=)	2, 4	USB 2.0 ports quantity	1
ID-card copy function	2,4	Network	
		Wi-Fi *	v
Edge erase function	•	Ethernet LAN *	v
Scanning		Cabling technology	10/100/1000Base-T(X)
Duplex scanning *	 Image: A set of the set of the	Ethernet LAN data rates	10,100,1000 Mbit/s
Scanning *	Colour scanning	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Optical scanning resolution *	600 x 600 DPI	Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES,
Optical scanning resolution (black)	300 x 600 ppi		WPA-PSK DHCP, ARP+PING, Auto IP, WINS,
Optical scanning resolution (colour)		Supported network protocols (IPv4)	Bonjour(mDNS), HTTP, HTTPS, POP,
Maximum scan resolution	9600 x 9600 DPI		LPD, RAW, Port9100, IPP, IPPS, WSD
Scanner type * Scan to	Flatbed & ADF scanner Cloud, E-mail, FTP, PC, USB	Supported network protocols (IPv6)	DHCPv6, Bonjour(mDNS), HTTP, HTTPS, POP, LPD, RAW, Port9100,
Scan speed (colour)	13 ppm		IPP, IPPS, WSD
Scan speed (black)	38 ppm	Management protocols	SNMPv1, SNMPv3
Duplex scan speed (colour)	26 ppm	Email protocols	Pop, SMTP
Duplex scan speed (black)	70 ppm	IP address filtering	1
Image formats supported	JPEG, TIFF		Apple AirPrint, Canon PRINT
Document formats supported	PDF	Mobile printing technologies	Business, Google Cloud Print, Mopria Print Service
Input colour depth	24 bit		
Output colour depth	24 bit	Performance	
Greyscale levels	256	Card reader integrated	×
Scan drivers	ICA, TWAIN, WIA	Internal memory *	1024 MB
Fax		Built-in processor	✓
Faxing *	Mono faxing	Processor frequency	800 MHz
Fax resolution (black)	400 x 400 DPI	Design	
Fax transmission speed	3 sec/page	Product colour *	Black, White
Modem speed	33.6 Kbit/s	Market positioning *	Business
Fax memory	512 pages	Built-in display *	1
Auto-redialing		Display	LCD
Fax speed dialing (max numbers)	281	Display diagonal	12.7 cm (5")
Fax forwarding	<i>•</i>	Touchscreen	 Image: A set of the set of the
Error Correction Mode (ECM)	4	Control type	Touch
Fax dual access	4	Colour display	 Image: A start of the start of
Multiple-destination sending	1	Power	
Features		Power consumption (standby)	10 W
Recommended duty cycle	750 - 4000 pages per month	Power consumption (sleep)	0.9 W
Maximum duty cycle *	80000 pages per month	Energy Star Typical Electricity	1.2 kWh/week
Number of print cartridges *	1	Consumption (TEC)	
Printing colours *	Black	AC input voltage	220 - 240 V
Page description languages	PCL 5e, PCL 6, PostScript, UFRII	AC input frequency	50 - 60 Hz
Printer fonts	PCL, PostScript	System requirements	
Number of printer fonts	181	Windows operating systems	Windows 10, Windows 7, Windows
Number of PCL fonts	45	supported	8, Windows 8.1 Mac OS X 10.10 Yosemite, Mac OS X
Number of PostScript fonts	136	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Input & output capacity		Mac operating systems supported	Sierra, Mac OS X 10.8 Mountain
Total number of input trays *	1		Lion, Mac OS X 10.9 Mavericks
Total input capacity *	250 sheets	Linux operating systems supported	✓ Windows Server 2008, Windows
Total output capacity *	150 sheets	Server operating systems supported	Windows Server 2008, Windows Server 2012, Windows Server 2016
Multi-Purpose tray			
	v	Operational conditions	
	1	Operational conditions Operating relative humidity (H-H)	20 - 80%

Weight & dimensions	
Width	453 mm
Depth	464 mm
Height	392 mm
Weight	16.9 kg
Other features	
Fonts included	✓



4549292090406

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.