Canon

Canon imageFORMULA DR-C230 Arkkisyöttöskanneri 600 x 600 DPI A4 musta

Tuotemerkki : Canon   **Tuoteperhe:** imageFORMULA   **Tuotekoodi:** 2646C003

Tuotteen nimi : DR-C230

Canon imageFORMULA DR-C230. Skannauksen enimmäiskoko: 216 x 3000 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, Lähdön värisyvyys: 24 bittiä. Skanneirtyyppi: Arkkisyöttöskanneri, Tuotteen väri: musta. Anturin tyyppi: CMOS CIS, Päivittäinen käyttöjakso (maks.): 3500 sivua, Valonlähde: RGB LED. Vakiosyöttökapasiteetti (arkkia): 60 arkkia. Suurin ISO A-luokan paperikoko: A4, Tuetut skannausmediatyypit: Käyntikortti, Muovikortti, Media paksuus (min.): 0,06 mm

Scanning

Maximum scan size *	216 x 3000 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Output colour depth	24 bit
Output greyscale depth	8 bit
Greyscale levels	256
ADF scan speed (b/w, A4)	30 ppm
ADF scan speed (colour, A4)	30 ppm
Duplex ADF scan speed (b/w, A4)	60 ipm
Duplex ADF scan speed (colour, A4)	60 ipm

Design

Scanner type *	Sheet-fed scanner
Product colour *	Black
Built-in display *	✘

Performance

Sensor type *	CMOS CIS
Light source	RGB LED
Daily duty cycle (max) *	3500 pages
Scan drivers	ISIS, TWAIN

Input capacity

Standard input capacity	60 sheets

Paper handling

Scanning media types supported	Business Card, Plastic Card
Multi feed detection	✔
Maximum ISO A-series paper size *	A4
Media thickness (min)	0.06 mm
Maximum scan width	21.6 cm
Maximum scan length	3 m

Ports & interfaces

USB version	2.0
Standard interfaces	USB 2.0

Power

Power supply type *	AC
Power consumption (typical)	19 W
Power consumption (standby)	1.4 W
Power consumption (off)	0.1 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Weight & dimensions

Width	291 mm
Depth	253 mm
Height	231 mm
Weight	2.8 kg

Packaging content

Cables included	AC, USB
AC adapter included	✔

Sustainability

Sustainability certificates	ENERGY STAR

Ports & interfaces		System requirements	
USB port *	✔	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
		Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
		Server operating systems supported	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016

Operational conditions	
Operating temperature (T-T)	10 - 32.5 °C
Operating relative humidity (H-H)	20 - 80%

Other features	
Scan media weight	27 - 209 g/m²
Compliance certificates	RoHS

Logistics data	
Harmonized System (HS) code	84716070

4528472107882