



# Canon imageFORMULA M40 1200 x 1200 DPI

Brand : Canon

Product family:  
imageFORMULA

Product code: 2289V962

Product name : M40

Scanner for imagePROGRAF MFP M40, SingleSensor (CIS), 1200dpi, 16.7M RGB/24-bit, 256 level greyscale, 22" LCD Touchscreen Monitor, SuperSpeed USB 3.0 Interface

[Canon imageFORMULA M40 1200 x 1200 DPI:](#)

## Canon imagePROGRAF MFP M40 Solution

### Designed for practicality and usability

The imagePROGRAF MFP M40 Solution is a total workflow system for anyone who needs to scan, copy, archive and distribute large format documents quickly and easily with remarkable accuracy and detail.

- SingleSensor (CIS) for high quality and accurate scanning
- Bi-directional LED light system for optimum object illumination and instant-on response
- Up to 13 inches per second scanning
- 1200dpi optical resolution
- 22" LCD Touch screen interface
- Next generation SmartWorks MFP Software for intuitive and flexible operation
- Scan to PDF, JPEG and TIFF up to 15m in length



|                                   |                       |                                     |  |
|-----------------------------------|-----------------------|-------------------------------------|--|
| <b>Scanning</b>                   |                       | <b>Ports &amp; interfaces</b>       |  |
| Maximum scan size *               | 1067 x 15000 mm       | Standard interfaces                 | USB 3.2 Gen 1 (3.1 Gen 1)  |
| Optical scanning resolution *     | 1200 x 1200 DPI       | <b>Power</b>                        |  |
| Colour scanning                   | ✓                     | Power supply type *                 | AC   |
| Duplex scanning *                 | ✗                     | Power consumption (typical)         | 24 W   |
| Input colour depth                | 24 bit                | Power consumption (standby)         | 5 W  |
| Film scanning                     | ✗                     | AC input frequency                  | 50 - 60 Hz   |
| Greyscale levels                  | 256                   | Input voltage                       | 100-240 V  |
| Black/white scanning colour modes | Grayscale             | <b>Packaging content</b>            |  |
| <b>Design</b>                     |                       | Bundled software                    | SmartWorks MFP V3.5  |
| Display                           | LCD                   | <b>System requirements</b>          |  |
| Display diagonal                  | 55.9 cm (22")         | Windows operating systems supported | Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 |
| Touchscreen                       | ✓                     |                                     |  |
| <b>Performance</b>                |                       |                                     |  |
| Sensor type *                     | CIS                   |                                     |  |
| Scan file formats                 | JPG, PDF, TIFF        |                                     |  |
| <b>Ports &amp; interfaces</b>     |                       |                                     |  |
| USB port *                        | ✓                     |                                     |  |
| USB version                       | 3.2 Gen 1 (3.1 Gen 1) |                                     |  |
|                                   |                       | <b>Operational conditions</b>       |  |
|                                   |                       | Operating temperature (T-T)         | 10 - 35 °C   |
|                                   |                       | Operating relative humidity (H-H)   | 35 - 80%   |
|                                   |                       | <b>Other features</b>               |  |
|                                   |                       | Compliance certificates             | RoHS   |
|                                   |                       | Certification                       | CE, FCC, VCCI, UL, CB, CCC   |



8714574591056

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.