



## DELL 407-BBOK lähetin-vastaanotinmoduuli Valokuitu 10000 Mbit/s SFP+

**Tuotemerkki :** DELL

**Tuotekoodi:** 407-BBOK

**Tuotteen nimi :** 407-BBOK

DELL 407-BBOK. SFP-vastaanottimen tyyppi: Valokuitu, Tiedonsiirron enimmäisnopeus: 10000 Mbit/s, PCI-väylä: SFP+. Yhteensopivat tuotteet: - PowerEdge C4130 - PowerEdge C4140 - PowerEdge C6320P - PowerEdge C6420 - PowerEdge FC430 -...

Performance		Features
SFP transceiver type *	Fiber optic	- PowerEdge C4130 - PowerEdge C4140 - PowerEdge C6320P - PowerEdge C6420 - PowerEdge FC430 - PowerEdge FC630 - PowerEdge FC640 - PowerEdge FC830 - PowerEdge M640 - PowerEdge M640 VRTX - PowerEdge R200 - PowerEdge R220 - PowerEdge R230 - PowerEdge R240 - PowerEdge R300 - PowerEdge R320 - PowerEdge R330 - PowerEdge R340 - PowerEdge R410 - PowerEdge R415 - PowerEdge R420 - PowerEdge R430 - PowerEdge R440 - PowerEdge R510 - PowerEdge R515 - PowerEdge R520 - PowerEdge R530 - PowerEdge R540 - PowerEdge R610 - PowerEdge R620 - PowerEdge R630 - PowerEdge R640 - PowerEdge R6415 - PowerEdge R710 - PowerEdge R715 - PowerEdge R720 - PowerEdge R720xd - PowerEdge R730 - PowerEdge R730XD - PowerEdge R730xd XL - PowerEdge R740 - PowerEdge R740XD - PowerEdge R740xd2 - PowerEdge R7415 - PowerEdge R7425 - PowerEdge R805 - PowerEdge R810 - PowerEdge R815 - PowerEdge R820 - PowerEdge R840 - PowerEdge R900 - PowerEdge R905 - PowerEdge R910 - PowerEdge R920 - PowerEdge R930 - PowerEdge R940 - PowerEdge R940xa - PowerEdge T130 - PowerEdge T140 - PowerEdge T330 - PowerEdge T340 - PowerEdge T410 - PowerEdge T420 - PowerEdge T430 - PowerEdge T440 - PowerEdge T610 - PowerEdge T620 - PowerEdge T630 - PowerEdge T640 - PowerEdge T710 - PowerEdge VRTX - PowerEdge XR2 - PowerVault DL2100 - PowerVault DL2200 - PowerVault DL2300 - PowerVault DR4100 - PowerVault DX6104 CSN - PowerVault DX6112 SN - PowerVault NX3000 - PowerVault NX3200 - PowerVault NX3300 - PowerVault NX400 - PowerVault NX440
Maximum data transfer rate *	10000 Mbit/s	
Interface type *	SFP+	
Fiber optic connector	LC	
SFP transceiver standard	SR	
Maximum transfer distance	500 m	
Networking standards	IEEE 802.3	
Cabling technology	10GBase-SR	
Fiber ports quantity	2	
		Compatible products
Logistics data		
Harmonized System (HS) code		85369010




4053162891005



5397063819591



0506016389936



506016389936

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.