

## Lenovo 4X91H02421 interface hub USB Type-C 5000 Mbit/s Black

Brand : Lenovo

Product code: 4X91H02421

Product name : 4X91H02421

- 1. Max 1 external display HDMI (4K@30Hz) or VGA Full HD (1920x1080p)
- 2. 2 x USB-A 3.1 Gen1 ports (up to 5 Gbps)
- 3. 1 x USB-C 3.1 Gen1 port for data synchronisation (up to 5 Gbps)
- 4. 1 x RJ45 Ethernet port (10/100/1000 Mbps)
- 5. USB-C 3.0 power delivery (5V/9V/20V up to 3A, 60W Maximum) Select USB-C 4K Mobile Hub

## Lenovo 4X91H02421 interface hub USB Type-C 5000 Mbit/s Black:

Lenovo Select USB-C 4K Mobile Hub expands the capabilities of ultrabook. With USB-C passthrough power, you can connect and charge your ultrabook or USB accessories. Get a second screen experience and connect via HDMI (4K @ 30 Hz) or VGA Full HD (1920x1080p) video for improved productivity. With a compact design, it is easy to carry and eliminates the your needs for video adapter and dongles.





## Ports & interfaces

Ports & interfaces		Power	
Host interface *	USB Type-C	Power consumption (max)	13.5 W
Hub interfaces *	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1	System requirements	
	Gen 1) Type-C, VGA	Windows operating systems supported	Windows 10
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Width	136 mm
HDMI ports quantity	1	Depth	78 mm
VGA (D-Sub) ports quantity	1	Height	16 mm
Ports quantity *	6	Weight	110 g
Ethernet LAN (RJ-45) ports	1	Packaging data	
Features		Quantity per pack	1 pc(s)
Data transfer rate *	5000 Mbit/s	Package width	15 mm
Maximum refresh rate	60 Hz	Package depth	81 mm
Supported graphics resolutions	2048 x 1152	Package height	27 mm
Maximum resolution (HDMI)	3840 x 2160 pixels	Package weight	190 g
Product colour	Black	Package type	Box
USB Power Delivery (USB PD)	✓	Operational conditions	
USB Power Delivery revision	3.0	Minimum operating temperature	10 °C
USB Power Delivery up to	60 W	Maximum operating temperature	40 °C
Certification	CB, CE, FCC, ICE, RCM, VCCI, KCC, BSMI, EAC, Ukraine DoC	Operating relative humidity (H-H)	5 - 95%
Network		Technical details	
	Circohit Ethernot	Warranty period	1 year(s)
Ethernet interface type	Gigabit Ethernet		
Ethernet LAN data rates	10,100,1000 Mbit/s		





195892036043

0195892036043

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.