

Lindy 4 Port USB 3.2 Type C Hub with On/Off Switches

Brand: Lindy Product code: 43383

Product name: 4 Port USB 3.2 Type C Hub with On/Off

Switches

4 Port USB 3.2 Type C Hub with On/Off Switches

Lindy 4 Port USB 3.2 Type C Hub with On/Off Switches:

The Lindy 4 Port USB 3.2 type C Hub provides convenient access and effective power management for USB Type A peripherals and storage devices. Capable of data transfer speeds of up to 5Gbps, the hub is also backwards compatible with USB 2.0 and 1.1.

The hubs individual On/Off switching ports can help reduce overall power consumption and are perfect for accessing external hard drives or other periodically used devices. An optional power supply can be connected for use with high current USB devices.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.





Ports & interfaces		Packaging data	
Host interface * Hub interfaces * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ports quantity *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C USB 3.2 Gen 1 (3.1 Gen 1) Type-A 4	Quantity per pack Package width Package depth Package height Package weight	1 pc(s) 174 mm 194 mm 15 mm 60 g
Features		Package type	Polybag
Data transfer rate *	5000 Mbit/s	Packaging content	
Product colour	Grey Acrylonitrile butadiene styrene (ABS), Aluminium, Polycarbonate	Manual	✓
Housing material		Operational conditions	
Cable type Cable length Certification	(PC) Round cable 0.3 m CE, FCC, RoHS & REACH, CP65	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T)	0 °C 50 °C 0 - 50 °C 0 - 60 °C
Power		Operating relative humidity (H-H)	0 - 85%
Power supply type	USB	Sustainability	
Weight & dimensions		Sustainability compliance	✓
Width Depth Height Weight	100 mm 30 mm 9 mm 42 g	Technical details Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS



4002888433839

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.