## Lindy VGA and Audio to HDMI Converter

Brand : Lindy

Product code: 38284

Product name : VGA and Audio to HDMI Converter

- Converts and combines VGA video and analogue audio signals into a HDMI signal
- Supports resolutions up to 1920x1080@60Hz
- Perfect for connecting older VGA computers to a HDMI display
- Powered by USB, simple plug and play installation
- 2 Year Warranty

VGA and Audio to HDMI Converter

## Lindy VGA and Audio to HDMI Converter:

The Lindy VGA and Audio to HDMI Converter combines analogue video and stereo audio signals and converts them into a HDMI signal, perfect for using legacy PC and AV equipment with HDMI displays. It supports resolutions up to 1920x1080. The integrated USB cable can be connected to a USB port or USB power supply to power the converter.

The converter is also ideally suited for travelling due to its compact, lightweight form factor and convenient Plug and Play installation.

Lindy VGA and Audio to HDMI Converter. Connector 1: VGA (D-Sub) + 3.5mm, Connector 2: HDMI + USB, Connector 1 gender: Male. Weight: 81 g, Width: 45 mm, Depth: 45 mm. Quantity per pack: 1 pc(s), Package width: 176 mm, Package height: 194 mm





Features		<b>Operational conditions</b>	
Connector 1 form factor	Straight	Operating relative humidity (H-H)	10 - 85%
Connector 2 form factor	Straight USB VGA (D-Sub) + 3.5mm HDMI + USB	Certificates	
Power source		Certification	CE, FCC, RoHS & REACH, CP65
Connector 1 *			, · · · · · · · · · · · · · · · · · ·
Connector 2 *		Weight & dimensions	
Connector 1 gender *	Male	Weight	81 g
Connector 2 gender *	Female	Width	45 mm
HDMI version	1.3	Depth	45 mm
Maximum resolution	1920 x 1080 pixels	Height	16 mm
Data transfer rate	4.95 Gbit/s 60 Hz Black AG02EX	Packaging data	
Maximum refresh rate		Package width	176 mm
Product colour		Package height	194 mm
Chipset		Package weight	120 g
Jacket material	Polyvinyl chloride (PVC)	Package type	Polybag
Plug and Play	✓	5 51	,
Converter type	Active video converter	Packaging content	
Operational conditions		Quantity per pack	1 pc(s)
• Operating temperature (T-T)	0 - 70 °C	Manual	1
Storage temperature (T-T)	0 - 60 °C	Logistics data	
		Harmonized System (HS) code	84733080



4002888382847

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.