



APC Smart-UPS RT 6000VA, 230V, 8x IEC 60320 C13 & 4x IEC Jumpers & 2x IEC 60320 C19 outlets

Brand : APC

Product code: SURT6000XLI

Product name : Smart-UPS RT 6000VA, 230V, 8x IEC 60320 C13 & 4x IEC Jumpers & 2x IEC 60320 C19 outlets

Smart-UPS RT 6000VA, 230V, 8x IEC 60320 C13 & 4x IEC Jumpers & 2x IEC 60320 C19 outlets

[APC Smart-UPS RT 6000VA, 230V, 8x IEC 60320 C13 & 4x IEC Jumpers & 2x IEC 60320 C19 outlets:](#)

High density, double-conversion on-line power protection with scalable runtime.
APC Smart-UPS RT 6000VA, 230V, 8x IEC 60320 C13 & 4x IEC Jumpers & 2x IEC 60320 C19 outlets.
Output power capacity: 6 kVA, Output power: 4200 W, Surge energy rating: 480 J. Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 5.3 min, Typical backup time at half load: 15.8 min. Product colour: Black. Certification: C-tick,CE,EN 50091-1,EN 50091-2,EN 55022 Class A,EN 60950,EN 61000-3-2,GOST,VDE. Width: 130 mm, Depth: 660 mm, Height: 432 mm



Features		Operational conditions	
Output power capacity *	6 kVA	Storage relative humidity (H-H)	0 - 95%
Output power *	4200 W	Certificates	
Surge energy rating	480 J	Certification	C-tick,CE,EN 50091-1,EN 50091-2,EN 55022 Class A,EN 60950,EN 61000-3-2,GOST,VDE
Emergency Power Off (EPO)	✓	Weight & dimensions	
Noise level	55 dB	Width	130 mm
Audible alarm(s)	✓	Depth	660 mm
Battery		Height	432 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	54.4 kg
Typical backup time at full load	5.3 min	Packaging data	
Typical backup time at half load	15.8 min	Package weight	63.6 kg
Battery recharge time	2.5 h	Logistics data	
Design		Harmonized System (HS) code	85078000
Product colour *	Black	Total carbon footprint (kg of CO2e)	7746.6
Operational conditions		Other features	
Operating temperature (T-T)	0 - 40 °C	I/O ports	8 x IEC 320 C13; 2 x IEC 320 C19
Storage temperature (T-T)	-15 - 45 °C	Interface	DB-9 RS-232
Operating relative humidity (H-H)	0 - 85%	Dimensions (WxDxH)	432 x 660 x 130 mm
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Package dimensions (WxDxH)	603 x 980 x 347 mm



4053162303010



0731304240174



731304240174

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.