



TP-Link TL-SF1005P Hallitsematon Fast Ethernet (10/100) Power over Ethernet -tuki musta

Tuotemerkki : TP-Link

Tuotekoodi: TL-SF1005P V1

Tuotteen nimi : TL-SF1005P

TP-Link TL-SF1005P. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Fast Ethernet (10/100), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. Täysin kaksipuolinen. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 1 Gbit/s. Verkkostandardit: IEEE 802.3af, IEEE 802.3x. DC-syöttöjännite: 53.5 V. Power over Ethernet -tuki



Management features		Power	
Switch type *	Unmanaged	Power supply included *	✗
Ports & interfaces		AC input voltage	220 V
Basic switching RJ-45 Ethernet ports quantity *	5	AC input frequency	50 Hz
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	DC input voltage	53.5 V
Network		Input current	1.31 A
Networking standards *	IEEE 802.3af, IEEE 802.3x	Power consumption (max)	74 W
10G support *	✗	Power over Ethernet (PoE)	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 100BASE-T	Power over Ethernet (PoE) *	✓
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Power over Ethernet plus (PoE+) ports quantity	4
Full duplex	✓	Total Power over Ethernet (PoE) budget	67 W
Half duplex	✓	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	0 - 40 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-40 - 70 °C
Auto-negotiation	✓	Operating relative humidity (H-H)	10 - 90%
MAC address auto-learning supported	✓	Storage relative humidity (H-H)	5 - 90%
MAC address auto-aging supported	✓	Heat dissipation	252.34 BTU/h
Data transmission		Weight & dimensions	
Switching capacity *	1 Gbit/s	Width	99.8 mm
Forwarding rate	0.744 Mpps	Depth	98 mm
MAC address table *	2000 entries	Height	25 mm
Store-and-forward	✓	Packaging content	
Jumbo frames support	✓	User guide	✓
Jumbo frames	2000	Packaging data	
		AC adapter included	✓

Design		Packaging data	
Rack mounting *	✘	Package type	Box
Stackable *	✘	Package width	131 mm
Product colour	Black	Package depth	196 mm
LED indicators	✔	Package height	121 mm
		Package weight	760 g
Performance		Sustainability	
Maximum cable length	100 m	Sustainability compliance	✔
Fanless	✔		
Power		Certificates	
Power source *	DC/PoE	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
		Logistics data	
		Harmonized System (HS) code	85176990



6935364083199



6935364083205



0845973083199



845973083199

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.